

## Irrigation system







### Rain gun AY-1050C

#### AnYou



Due to the brass core and whole body painting, Rain gun sprinkler 2 inch is durable. Spray radius is long, radius 31-63.5m. This rain gun represent our capacity to integrate innovative technology, performance and reliability. Especially designed for pivot end gun irrigation, environmental applications, sports field applications.

### 1. Application

- (1) Pivot End Gun Irrigation
- Traveler Irrigation
- Solid Set Irrigation
- Corn, Sugar Cane, Pineapple, Pastures, etc.
- (2) Environmental Applications
- Feedlot Dust Suppression & Cooling
- Waste water Applications
- Mining Dust Suppression
- (3) Sports Field Applications
- Turf Irrigation
- Synthetic Turf Cooling & Conditioning



#### 2. Product Feature

- (1) Key parts: brass core
- (2) Whole body painting, more durable and beautiful
- (3) Spray better with special part
- (4) Long distance spray radius
- (5) Good welding
- (6) It is the circle operation, the angle is adjustable from 0 degree to 360 degree
- (7) No need of land leveling



# Rain gun AY-1050C

Rain gun AY-1050C	Pressure	Flow rate	Radius
Nozzle (mm)	(bar)	( M³/H)	(M)
20	2	22.2	31
	3	26.7	36
	4	31.5	41.2
	5	35.1	44
	6	38.1	47.1
	7	42.2	49
22	2	26.8	33
	3	33.5	37.5
	4	37.9	43
	5	42.5	46
	6	46.5	49.5
	7	49.8	52
	2	31.8	34
	3	39.5	40
24	4	45.3	44.3
24	5	50.3	48
	6	54.6	52
	7	58.8	55.2
	2	37.5	36.6
26	3	45.7	42
	4	52.3	47
	5	58.9	51.5
	6	64.5	55
	7	69	58
28	2	43.2	37
	3	52.7	43
	4	61.1	49
	5	67.8	53.2
	6	74.6	57
	7	81	60
30	2	49.3	39
	3	60.5	45
	4	70	51
	5	78	55.8
	6	85.7	59
	7	92.8	63.5

Baoding Anyou Industry www.anyouirrigation.com



## AY-1050C-Short

AY-1050C-Short	Pressure	Flow rate	Radius
Nozzle (mm)	(bar)	( M³/H)	(M)
16	2	14.2	27
	3	17.5	32.2
	4	19.9	36
	5	22.8	39
	6	24.7	42.6
	7	26.6	44
18	2	17.9	29
	3	21.9	34
	4	25.5	38.4
	5	28.2	42
	6	30.9	45
	7	33.2	47.2
	2	22.2	31
20	3	26.7	36
	4	31.5	41.2
	5	35.1	44
	6	38.1	47.1
	7	42.2	49
22	2	26.8	33
	3	33.5	37.5
	4	37.9	43
	5	42.5	46
	6	46.5	49.5
	7	49.8	52
24	2	31.8	34
	3	39.5	40
	4	45.3	44.3
	5	50.3	48
	6	54.6	52
	7	58.8	55.2

